

# Declaration of performance

Product: ALU Modern  
(Fastening: Post attached on top of floor or with lateral fixation)

Intended use: Balustrade

Manufacturer: Räckesbutiken Sweden AB, Åkerslundsgatan 10,  
262 73 Ängelholm, Sweden

Compliance certification system: EN 1090-1:2009 + A1:2011

Notified body: RISE Research Institutes of Sweden

Notified body nbr: 0402

has performed initial audit and assessment of manufacturing control as well as ongoing monitoring of manufacturing control and has issued manufacturing control certificates; (FPC) nr: 0402 - CPR - SC0636-14


| Essential properties                                 | Performance                                                                                   | Harmonised technical specification |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------|------------------------------------|
| Geometric data (tolerances for dimensions and shape) | Geometric tolerances according to ISO7976-1-7976-2 and 1090-2 including measurement accuracy. | EN 1090-1:2009+A1:2011             |
| Weldability                                          | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Fracture toughness                                   | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Reaction to fire                                     | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Release of Cadmium                                   | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Radioactive radiation                                | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Longevity                                            | 20 µm                                                                                         | EN 1090-1:2009+A1:2011             |
| Execution class                                      | EXC2                                                                                          | EN 1090-1:2009+A1:2011             |
| Fire resistance                                      | NPD                                                                                           | EN 1090-1:2009+A1:2011             |
| Linear load capacity                                 | 0,5 kN/m                                                                                      | EN 1991-1-1/A, B, C1               |
| Fatigue                                              | NPD                                                                                           | EN 1090-1:2009+A1:2011             |

The performance of the above product complies with the declared properties listed in the above table.

This declaration of performance is issued under the sole responsibility of the above-mentioned manufacturer.

Signed for the manufacturer by:

11/09/25

  
Björn Johansson